



MINI PRINTER MECHANISMS

↻ 4" | ⚡ 5V

ELM4071-V10

Options

- Chipset UC33

Features

- Easy integration & light design
- Patented easy loading and easy door opening system
- Front and bottom paper loading
- Low consumption & noise

Applications

- ATM
- Automotive
- Cash Registers
- EFT POS
- Fiscal Printers
- Hand Held Terminals
- Measuring Instruments and Analysers
- Medical Equipment
- Taxi Meters

Specifications	ELM4071-V10
Print method	Thermal
Number of dots	864
Resolution (dots/mm)	8
Max Printing speed (mm/s)	100
Print resolution (dpi)	203
Sensor	Paper End
Media Type	Ticket
Paper width (mm)	114
Printing width (mm)	108
Min. paper thickness (µm)	63
Max. paper thickness (µm)	80
Paper loading	Easy Loading
Dimensions (WxDxH mm)	137.1 x 48.4 x 42.4
Weight (g)	140
Operating Voltage	5V
Voltage range (Logic/Head)	Logic: 5V ±5% / Dots : 24V ±10%
Paper detection	Opto sensor
Temperature detection	Thermistor
Head-up or Cover-open detection	Opto sensor
Connector Type	FPC



MINI PRINTER MECHANISMS

↔ 4" | ⚡ 5V

ELM4071-V10

Specifications

ELM4071-V10

Operating temperature

From -10° to 60°C

Storage temperature

From -25° to +70°C

Operating humidity

10% to 90% (no condensing)

TPH

50 km / 100M pulses

Certifications

ISO 9001:2015, ISO14001, ISO13485:2016 certified - RoHS compliant